C-BOX

Product Specification Sheet
Cross-reference: nVent SCHROFF 14575-167

14575-167

CompacPRO Desktop Case, Unshielded, 3 U, 84 HP, 391 mm

Rack height	3 U	**Material**	Aluminum
Width	471.0 mm	**Finish**	Powder Coated
Depth	391.0 mm	**Net weight**	4.0 kg
Height	147.1 mm	**Standard**	IEC 60297-3-103

Full specification

Rack Height	3U
Height	147.1mm
Rack Width	84HP
Width	471mm
Depth	391mm
Package Quantity	1
Usable Height	129.3mm
Usable Width	432mm
Front Frame Construction	Single Piece
Cooling Option	No
Complies With	IEC 60297-3-103
EMC Shielding	No
Finish	Powder Coated
Material	Aluminum
Product Family	CompacPRO
Product Type	Case
Protection Rating	IP20
Static Load	30kg
Type	Case for Individual Electronic Components
Net Weight	4kg

Items delivered

No.	Item	Qty
1	Side panel, Al extrusion, powder■coated, RAL 7016	2
2	Frame, Al die■cast, powder■coated, RAL 7016	2
3	Cover plate, Al, 1.5 mm, powder■coated, RAL 9006, with GND/earthing connection	1
4	Base plate with 4 rows of ventilation slots, Al, 1.5 mm, powder■coated RAL 9006, with earthing connection	1
5	Case foot with anti■slip protection, PC, black	4
6	Fixing adaptor for cover plate, prefitted	8
7	Assembly kit, also allows the fitting of a full■width front panel, two cover brackets or a rear panel	1

sheet-metal chassis.

Request a quote or a custom variant: contact us via the email above.

Specification data compiled from manufacturer catalog data (2026-11-14). Values subject to change without notice; verify critical dimensions before final mechanical design.