C-BOX

Product Specification Sheet
Cross-reference: nVent SCHROFF 20848-230

20848-230

Plug-In Unit U-Profile Front Panel for IEL, IET Type 2 Handle, 3 U, 14 HP, 2.5 mm, Al, Front Anodized, Rear Conductive

Rack height	3 U	**Net weight**	0.06 kg
Material	Aluminum	**Standard**	IEC 60297-3-102; IEEE 1101.10; IEC 60297-3-103; IEEE 1101.1/11
Finish	Anodized; Passivated		

Full specification

Rack Width	14HP
Package Quantity	1
Accessory Type	Front panel
Handle Type	IEL; IET; Trapezoid, Type 2
Mounting	Screw-on Front
Gasket Type	Textile EMC
Front Finish	Anodized
Rear Finish	Conductive
Treated Edges	No
Complies With	IEC 60297-3-102; IEEE 1101.10; IEC 60297-3-103; IEEE 1101.1/11
Depth (D)	2.5mm
EMC Shielding	No (Retrofittable)
Finish	Anodized; Passivated
Height (H)	128.4mm
Material	Aluminum
Product Type	Front Panel
Rack Height	3U
Type	Front Panel for Handle (PIU)
Width (W)	70.8mm
Net Weight	0.06kg

Items delivered

No.	Item	Qty
1	Front panel, U profile, Al, 2.5 mm, front anodized, rear conductive, 2 alignment pins pressed-in, stainless steel	1

www.c-box-tech.com · vincent_zhao@c-box-tech.com
C-BOX Electronic Technology Co., Ltd. · 19″ rack systems, subracks, guide rails and custom sheet-metal chassis.
Request a quote or a custom variant: contact us via the email above.

Specification data compiled from manufacturer catalog data (2026-11-14). Values subject to change without notice; verify critical dimensions before final mechanical design.