C-BOX

Product Specification Sheet
Cross-reference: nVent SCHROFF 21500-081

21500-081

EuropacPRO 19" Subrack Kit for Railway, Shielded, EN 50155, CompactPCI, 3 U, 84 HP, 235 mm

Rack height	3 U	**Finish**	Anodized; Passivated
Depth	9.25 mm	**Net weight**	2.042 kg
Material	Aluminum	**Standard**	IEC 60297-3-103; IEEE 1101.10; IEEE 1101.11; EN 50155 part 12.2.11

Full specification

Rack Height	3U
Package Quantity	1
Depth	9.25in
For Mounting	Backplane
Board Depth	160mm
Gasket Type	Textile EMC
Shock and Vibration Tolerance	5g (force)
Handle Included	Yes
Mounting	Rack
Complies With	IEC 60297-3-103; IEEE 1101.10; IEEE 1101.11; EN 50155 part 12.2.11
EMC Shielding	Yes
Finish	Anodized; Passivated
Material	Aluminum
Product Type	Subrack/Chassis
Rack Width	84HP
Static Load	15kg
Net Weight	2.042kg

Items delivered

No.	Item	Qty
1	Side panel type H with 19" support bracket (tox-cold welded); for EMC textile gasket	2
10	User manual	1
2	Front horizontal rail (H■KD)	1
3	Threaded inserts	4
4	Perforated strip	2
5	EMC cover plate, 175 T	2
6	EMC gasketing kit	1
7	Backplane kit – EMC shielding material	1
8	Handles	2
9	Assembly kit with self-locking screws	1

Request a quote or a custom variant: contact us via the email above.

Specification data compiled from manufacturer catalog data (2026-11-14). Values subject to change without notice; verify critical dimensions before final mechanical design.