C-BOX

Product Specification Sheet
Cross-reference: nVent SCHROFF 24572-357

24572-357

RatiopacPRO 19" Case, Retrofittable Shielding With Handles, 5 U (3-2), 28 HP, 255 mm

Rack height	5 U	**Material**	Aluminum
Width	164.4 mm	**Finish**	Passivated; Powder Coated
Depth	255.5 mm	**Standard**	IEC 60297-3-101; IEC 60297-3-102; IEEE 1101.1; IEEE 1101.10; IEEE 1101.11
Height	221.5 mm		

Full specification

Rack Height	5U
Rack Width	28HP
Depth	255.5mm
Package Quantity	1
Usable Height	201.25mm
Usable Width	148mm
Front Frame Construction	Handles; Horizontal Rails
Cooling Option	No
Complies With	IEC 60297-3-101; IEC 60297-3-102; IEEE 1101.1; IEEE 1101.10; IEEE 1101.11
EMC Shielding	No (Retrofittable)
Finish	Passivated; Powder Coated
Height	221.5mm
Material	Aluminum
Product Family	RatiopacPRO
Product Type	Case
Protection Rating	IP20
Static Load	25kg
Type	Case for Individual Electronic Components
Width	164.4mm

Items delivered

No.	Item	Qty
1	2 Side plate, Al, 1 mm, visible surfaces powder-coated, RAL	9006
2	3 Rear trim, Al die-cast, powder-coated, RAL	7016
2	3b Front handle, Al die-cast, powder-coated, RAL	7016
2	4 Horizontal rail, type H-LD, Al, visible surfaces powder-coated, RAL 7016	4

www.c-box-tech.com · vincent_zhao@c-box-tech.com
C-BOX Electronic Technology Co., Ltd. · 19″ rack systems, subracks, guide rails and custom sheet-metal chassis.
Request a quote or a custom variant: contact us via the email above.

Specification data compiled from manufacturer catalog data (2026-11-14). Values subject to change without notice; verify critical dimensions before final mechanical design.