C-BOX

Product Specification Sheet
Cross-reference: nVent SCHROFF 24813-278

24813-278

Frame Type Plug-In Unit PRO Kit, Shielded, Perforated, 1 Connector, 3 U, 28 HP, 227 mm

Rack height	3 U	**Finish**	Anodized; Passivated
Material	Aluminum		

Full specification

Rack Height	3U
Rack Width	28HP
Depth (D)	227mm
Handle Type	Trapezoid
Package Quantity	1
Gasket Type	Textile EMC
Rear Panel Type	Single Connector Cut-Out
Cover Plate Type	Cover Plate with Perforation for Guide Rails
Front Finish	Anodized
Rear Finish	Conductive
Cooling	Perforated
EMC Shielding	Yes
Finish	Anodized; Passivated
Material	Aluminum
Product Type	Cassette
Type	Frame Type Plug-in Units PRO
Gross Weight	0.971kg

Items delivered

No.	Item	Qty
1	Front panel, U profile anodised, rear conductive, alignment pin pressed-in	1
2	Handle, grey, PC, RAL 7035, UL 94 V-0, EN 45545-2, R22 - R24, HL3	1
4	Side panel, Al extrusion, colourless passivated, with groove for one PCB	2
6	EMC sealing (textile)	1
7	Assembly kit	1

www.c-box-tech.com · vincent_zhao@c-box-tech.com
C-BOX Electronic Technology Co., Ltd. · 19″ rack systems, subracks, guide rails and custom sheet-metal chassis.
Request a quote or a custom variant: contact us via the email above.

Specification data compiled from manufacturer catalog data (2026-11-14). Values subject to change without notice; verify critical dimensions before final mechanical design.