C-BOX

Product Specification Sheet
Cross-reference: nVent SCHROFF 30848-869

30848-869

Plug-In Unit, U-Profile Front Panel, for IEL, IET, Type 2 Handle, Shieldable, 3 U, 8 HP, Rear I/O, 2.5 mm, Al, Front Anodized, Rear Conductive

Rack height	3 U	**Finish**	Anodized; Passivated
Material	Aluminum	**Standard**	IEC 60297-3-102; IEEE 1101.10; IEC 60297-3-103; IEEE 1101.1/11

Full specification

Rack Width	8HP
Package Quantity	1
Accessory Type	Front panel
Handle Type	IEL; IET
Mounting	Screw-on Rear IO
Gasket Type	Textile EMC
Front Finish	Anodized
Rear Finish	Conductive
Treated Edges	No
Complies With	IEC 60297-3-102; IEEE 1101.10; IEC 60297-3-103; IEEE 1101.1/11
Depth (D)	2.5mm
EMC Shielding	No (Retrofittable)
Finish	Anodized; Passivated
Height (H)	128.4mm
Material	Aluminum
Product Type	Front Panel
Rack Height	3U
Type	Front Panel for Handle (PIU)
Width (W)	40.3mm
Gross Weight	0.037kg

Items delivered

No.	Item	Qty
1	U front profile, Al, 2.5 mm, front anodized, side and rear conductive	1
2	Alignment pin pressed in, St, alignment via perforated strip	1

www.c-box-tech.com · vincent_zhao@c-box-tech.com
C-BOX Electronic Technology Co., Ltd. · 19″ rack systems, subracks, guide rails and custom sheet-metal chassis.
Request a quote or a custom variant: contact us via the email above.

Specification data compiled from manufacturer catalog data (2026-11-14). Values subject to change without notice; verify critical dimensions before final mechanical design.